



WARRANTY
5
YEAR

-40~+40 C

PANEL SERIES

TLT-LP-20-70w



optional suspended installation

PRODUCT PARAMETERS

MODEL	SIZE (mm)	WATT(W)	LUMENS (100LM/W)	LUMENS (130LM/W)	BEAM ANGLE (H-V)	SDCM	DIMMING	ETL& CETL	DLC	CRI	POWER FACTOR	AVAILABLE CCT(K)
TLT-LP-20W	298X298	20W	2000	2600	120°	≤3/≤5	optional			>82	>0.9	3000~5000
TLT-LP-36W	603X603	36W	3600	4680	120°	≤3/≤5	optional	✓	✓			
TLT-LP-45W	603X603	45W	4500	5850	120°	≤3/≤5	optional	✓	✓			
TLT-LP-B36W	1213X298	36W	3600	4680	120°	≤3/≤5	optional	✓	✓			
TLT-LP-B45W	1213X298	45W	4500	5850	120°	≤3/≤5	optional	✓	✓			
TLT-LP-50W	1213X603	50W	5000	6500	120°	≤3/≤5	optional	✓	✓			
TLT-LP-70W	1213X603	70W	7000	9100	120°	≤3/≤5	optional		✓			

PACKAGE INFORMATION

MODEL	QTY/CTN	NET WEIGHT(KG)
20W	4	13.14
36W	2	7.2 - 7.4
45W	2	7.2 - 7.4
50W	2	13
70W	2	13

INFORMATION

Full range of products: Emergency, Sensor, 0-10V DIM, NON-DIM, Emergency with sensor, Emergency with 0-10 DIM etc can be flexible combination. (DIM without flickering).

Using wireless IR Remote Control cuts down installation and maintenance cost, best choice of intelligent emergency lighting system.

After leaving factory, the emergency battery turns itself into a dormant state to avoid electric discharge and leakage

ACCESSORIES



Remote Control



optional suspended installation