




WARRANTY
5
YEAR

IP65

-25~+40 °C

TRI-PROOF




PRODUCT PARAMETERS


MODEL	INPUT VOLTAGE (V)	POWER (W)	LUMENS (120LM/W)	LUMENS (140LM/W)	BEAM ANGLE (H-V)	AVAILABLE CCT(K)	CRI	ETL & CETL	DLC	THD	SDCM
TLT-TR-20W	90~305VAC	20W	2560	2800	270°	3000~5000K	≥82	✓	✓	<18%	≤3/≤5
TLT-TR-25W	90~305VAC	25W	3200	3500	270°	3000~5000K	≥82				
TLT-TR-36W	90~305VAC	36W	4600	5040	270°	3000~5000K	≥82	✓	✓		
TLT-TR-45W	90~305VAC	45W	5760	5300	270°	3000~5000K	≥82	✓	✓		
TLT-TR-60W	90~305VAC	60W	7680	8400	270°	3000~5000K	≥82		✓		
TLT-TR-70W	90~305VAC	70W	8960	9800	270°	3000~5000K	≥82	✓	✓		

THESE ARE PARAMETERS FOR THE BASIC MODELS. DIFFERENTS OPTIONS AND CUSTOMIZATIONS ARE AVAILABLE.
 2 EMERGENCY MODES WITH DIFFERENTS OPTIONS, 3 INSTALLATIONS MODES: SUSPENDING INSTALLATION, SCREWING INSTALLATION AND SURFACE MOUNT INSTALLATION.
 3 CONNECTION MODES INSTALLATIONS: PARALLEL CONNECTION WITH INPUT LINES, PARALLEL /SERIES CONNECTION WITHOUT INPUT LINES & SEAMLESS CONNECTION.

INSTALLATION



SUSPENDING INSTALLATION



SCREWING INSTALLATION



SURFACE MOUNT INSTALLATION


ACCESSORIES



HANGING KIT



METAL HOSE



BUCKLES